LPG DISTRIBUTION SYSTEM

(AUTO GAS STATION, INDUSTRIES, SATELLITE PLANT & MOTHER PLANT)



One Stop Engineering & Technology Services

LPG ROAD TANKER



LPG BOBTAIL



Standard: BS EN 13445

Capacity: 1. Road Tanker: 40m3(40,000ltr.)

2. Bobtail: 15m3 to 24m3(15,000ltr. to 24,000ltr.)

Operating Pressure: 10 Bar Design Pressure: 17 Bar Test Pressure: 26 Bar

Design Temperature: -20°C to +65°C

Manhole: DN - 400

Coating: Epoxy Primer Paint LPG Pump: Sliding Vane Flow Meter: Mass Flow Meter

Loading Hose: Flexible Hose with Flange

Level Gauge: Rochester, USA **Safety Relief Valve:** Rego, USA

Valves and Fittings: Liquid Withdrawal Valve, Filling Valve,

& Vapor In-out Valve

Corrosion Allowance: 1 mm (Standard)

Chassis Type: Can Be Single-Axle or Dual-Axle

Tare weight: 1. Road Tanker: 18.5 MT

2. Bobtail: 12 MT to 15 MT

Gross weight: 1. Road Tanker: 36.5 MT

2. Bobtail: 18MT to 25 MT

2. BODIGII: 10/01/10/25 /01/

Safety equipment: Fire Extinguishers, First Aid Kits, and

Other Safety Devices

Testing: Witness, Ultrasonic Test

Approved by: BUET, Department of Explosive

Certification: Testing Certification by Bureau Veritas

CONCERNS







LPG STORAGE TANK FOR ROAD TANKER



Capacity: 20MT/40m3/40,000 ltr.

Standard: BS EN 13445

Design Pressure: 17 bar

Test Pressure: 26 bar

Design Temperature: -20°C to +60°C **Approved By:** Explosive Department

ISO 9001: 2015 Certified

Design Approved By: BUET

NDT (Ultrasonic Test) By: Bureau Veritas

Hydraulic Test By: Bureau Veritas

Origin: Bangladesh

LPG STORAGE TANK FOR BOBTAIL



Capacity: 7.5MT/15m3/15,000 ltr.

12MT/24m3/24,000 ltr.

Standard: BS EN 13445

Design Pressure: 17 bar

Test Pressure: 26 bar

Design Temperature: -20°C to +60°C **Approved By:** Explosive Department

ISO 9001: 2015 Certified

Design Approved By: BUET

NDT (Ultrasonic Test) By: Bureau Veritas

Hydraulic Test By: Bureau Veritas

Origin: Bangladesh

APPROVAL/CERTIFICATION/LICENSE

















CORIOLIS MASS FLOW METER CG-50

✓ LPG Flow Meter: Mass flow, CG-50,

✓ Max Flow Rate: 60t/h

✓ Nominal Diameter: 50mm

✓ MWP.: 4MPa

✓ Zero Stability: 2.38kg/h

✓ Repeatability: 0.10%; Flange size 2"

✓ Liquid Accuracy: ±0.2%

⊘ Gas accuracy: ±0.5%

✓ Temp. Accuracy: ±1°C ±0.5% of reading

✓ Density Accuracy: ±0.002g/cm³

√ Fluid Temperature: '-70~+160°C

✓ End Connection Flange: DIN2635 PN40

Operating Voltage: 220VAC or 24VDC

Omm. & Output: RS485 Modbus RTU, Pulse

G.W.: 65kgs

Package Size: 865*715*430mm

✓ Certificate: CE, ATEX

Origin: Sealand, China

TRANSFER PUMP

✓ Type: Sliding Vane✓ Capacity: 10 m³/h

✓ Head: 25 bars (Max.)

✓ Working Pressure: 1.8 MPa

✓ Speed: 600 RPM✓ Motor: 5.5 kw

Working Temperature: 120°C (Max.)
 Flange Connections: DN-50, PN-40

✓ Temperature Range: -20 °C to +120 °C









- ⊘ Pioneer of LPG equipment supply in Bangladesh.
- Quick delivery, Installation and after sales support.
- ✓ Uninterrupted technical support by skilled manpower.
- ② Explosive license for manufacturing of LPG storage tank in Bangladesh.
- Successfully installed and commissioned more than 500 LPG Auto gas stations in all over the country.
- $\ensuremath{ \oslash}$ Operation & maintenance support from all divisional/zonal office.

OUR FACTORY FACILITY



LPG TANK MANUFACTURING PLANT

LPG PRESSURE VESSEL

Production Capacity: 10 Pcs Per month **Tank Capacity:** 10cbm up to 40 cbm

(10,000 ltr. to 40,000 ltr.)

Type: Aboveground, Underground & Mounded

Tank Orientation: Horizontal

Standard: EN-13445

LPG AUTO TANK

Production Capacity: 300 Pcs/month

Tank Capacity: 30 ltr. to 140 ltr.

Type: Cylindrical & Toroidal



MEETING









ROLLING WORK

V-NOTCH CUTTING

Welding UT TESTING

OUR CONTACT

Corporate Office

- SMET Services / Saad Motors Ltd
 2/2 Pallabi (5th Floor), Mirpur, Dhaka-1216
- Sale Support: 01765038392, 01704179393
- Customer Support: 01765038391, 01765038398
- After Sale Support: 01765038393, 01765038396 01765038392
- www.smetservices.com

Factory Office

- Saad Motors Ltd
 Plot: A-41, Kawnia, Barishal, Bangladesh
- 01704179369, 01704179361
- 01765038392
- www.smetservices.com



CONCERNS





